

BlueCat GEN4 Appliances

BlueCat GEN4 appliances supports the needs of the Enterprise that requires a full-featured appliance coupled with high performance, dual-power AC/DC supplies, and lights-out management.

BlueCat GEN4 appliances represent BlueCats's latest generation of rack-optimized system solutions that support the highest performance demands and throughput for BlueCat Address Manager and BlueCat DNS/DHCP Server application. BlueCat GEN4 appliances are high-performance, 1-socket 1U rack servers with the enhanced computing power, business scalability, simplified management, data protection, and security features that make them an ideal choice for the most demanding deployments.

Benefits

- Full-featured appliance solution for both hardware and software
- Increased memory and disk capacity compared to Generation 3 appliances
- Multi-core scalable processor
- Cost-effective, rack-mountable servers
- 64-bit architecture
- Redundant power AC, DC optional

- Light-out management (iDRAC9 enterprise)
- Ready for Enterprise DNS
- Optional Fibre connectivity (10GB SPF+/DA)
- Improved QPS/LPS performance
- Dual Power is standard across the appliance range

Hardware Specifications

| BlueCat GEN | I4 Appliances | | | | | |
|-------------------------------|-----------------------------|--------------------------------|--|--|---|--|
| Model | | XMB3 | 2000 | 4000 | 5000 | 7000 |
| Supported Platforms | | BDDS | BDDS-25 | BDDS-50 | BAM-5000, BDDS-75 | BAM-7000, BDDS-125 |
| Performance Specifications | Queries per Second (QPS) | 15,000 | 60,000 | 150,000 | 230,000 | 270,000 |
| | Leases per Second (LPS) | 110 | 1000 | 1500 | 2000 | 2300 |
| Processor | CPU | Intel Atom® Processor E3827 | Intel® Pentium® Gold G5500 Processor | Intel® Xeon® E-2124 | Intel® Xeon® E-2136 | 2 x Intel Xeon Silver 4114 |
| | CPU Speed | 3.8 GHz | 3.8 GHz | 3.3 GHz | 3.3 GHz | 2.2 GHz |
| | CPU Total Cores & Threads | 2C/4T | 2C/4T | 4C/4T | 6C/12T | 20C/40T |
| | Hyper Threading Support | N/A | Yes | N/A | Yes | Yes |
| Memory | Memory | 4 GB | 8 GB | 16GB | 32 GB | 64 GB |
| | Memory Speed | 1333 MT/s | 2666 MT/s | 2666 MT/s | 2666 MT/s | 2666 MT/s |
| Power | PSU | DC + 12V Input | Dual AC PSU(s) | Dual AC PSU(s) | Dual AC PSU(s) | Dual AC PSU(s) |
| | PSU Wattage | N/A | 350 w | 350 w | 350 w | 495 w |
| | PSU Swappable | N/A | Yes | Yes | Yes | Yes |
| | PSU DC Option | N/A | N/A | N/A | N/A | Yes |
| | UPS Agent Support | NO | NO | NO | NO | Yes* |
| Storage | Storage Type | HDD | HDD + SDXC | HDD + SDXC | HDD + SDXC | SSD + SDXC |
| | Storage Capacity | (1) x 500 GB SATA | (1) x 1 TB 7200 SATA (1) x 16 GB SHDC Cards | (1) x 1 TB 7200 SATA (1) x 16 GB SHDC Cards | (2) x 1 TB 7200 SATA (RAID 1) (1) x 16 GB SHDC Cards | (2) x 960 GB (RAID 1) SSD Main Array |

^{*}Available November 2019

| | | | | | | (2) x 240 GB (RAID 1) M2 SSD BOSS (2) x 16 GB (Raid 1) SHDC Cards |
|--|-------------------------|---|-------------------------------------|--------------------------------------|--|---|
| | Raid Configuration | N/A | N/A | N/A | RAID1 - PERC H330 Controller | RAID1 - PERC H730P Controller |
| Network | Network Card | (2) x Intel i210IT DP | (2) x Broadcom 5720 DP | (2) x Broadcom 5720 DP | (2) x Broadcom 5720 DP | (1) x Intel i350 QP |
| | Fibre Option Support | N/A | N/A | N/A | Yes – replaces network card | Yes – replaces network card |
| | Optional Fibre Card | N/A | N/A | N/A | (2) x Intel X710 Dual Port 10 GB DA/SFP+ | Intel X710 Quad Port 10 GB DA/SFP+ |
| | Network Ports | (4) x 1 GB (Intel) | (4) x 1 GB (Broadcom) | (4) x 1 GB (Broadcom) | (4) x 1 GB (Broadcom) | (4) x 1 GB (Intel) |
| | IDRAC Port | N/A | Yes | Yes | Yes | Yes |
| | IDRAC Hardware | N/A | iDRAC9 Enterprise | iDRAC9 Enterprise | iDRAC9 Enterprise | iDRAC9 Enterprise |
| Rack and Mounting Specifications | Mounting Kit | Special Kit for mount 2xXMB3 is 1U rack | ReadyRails Static Rails 2/4 Post | ReadyRails Sliding without CMA | ReadyRails Sliding without CMA | ReadyRails Sliding with CMA |
| | Depth | 155.00 mm | 508.00 mm | 508.00 mm | 508.00 mm | 808.51 mm |
| | Width | 190.0 mm | 482.0 mm | 482.0 mm | 482.0 mm | 482.0 mm |
| | Height | 42.0 mm | 42.8 mm | 42.8 mm | 42.8 mm | 42.8 mm |
| Warranty | Standard | 5 Years, next business day | 5 Years, next business day | 5 Years, next business day | 5 Years, next business day | 5 Years, next business day |
| | Optional | N/A | 4 Hours | 4 Hours | 4 Hours | 4 Hours |



© 2019 BlueCat Networks (USA) Inc. and/or its affiliates. All rights reserved. BlueCat, BlueCat Networks, the BlueCat logo, BlueCat DNS/DHCP Server, BlueCat Address Manager, BlueCat Device Registration Portal and BlueCat Threat Protection are trademarks of BlueCat Networks (USA) Inc. and/or its affiliates. All other product and company names are trademarks or registered trademarks of their respective holders. BlueCat reserves the right to change, modify, transfer or otherwise revise this publication without notice.